

**Protects
against oil stains
Interior and exterior use**

**Maximum
protection against
stains, mould and
mildew**

**ULTRA
GROUT
SEALER**

6/9 Hoyle Avenue, Castle Hill NSW 2154
Tel: 1300 195 670
sales@rodauxsurfacecare.com.au
www.rodauxsurfacecare.com.au





Ultra Grout Sealer

PRODUCT DESCRIPTION

Ultra Grout sealer is a spray sealer that can be used to seal grout joints, splashbacks, and wall tiles. Ultra grout sealer is extremely easy to apply and provides maximum protection against stains and prevents mould and mildew. The sealer dries exceptionally quickly and still maintains the natural appearance.

FEATURES & BENEFITS

- Able to be used for interior and exterior use.
- Easy to use & Quick Drying
- Great for new bathrooms, benchtops, splashbacks, wall tiles and grout joints.
- Protects against oil stains and prevents mould and mildew.
- Quickly penetrates and maintains natural appearance of surface.
- Easy to clean surface.
- Australian made and tested for Australian conditions.

PACKAGING:

- 300 grams

COVERAGE

Coverage depends on the porosity, temperature & method of application. One 300g canister will cover approximately up to 150 to 200 lineal meters (20 square meters).

SUITABLE FOR:

- All Grout joints.
- Kitchens splashbacks.
- Bathrooms.
- All Natural Stones.
- Benchtops.
- Wall tiles.

NOT SUITABLE FOR:

- Non porous surfaces.
- Epoxy or resin based grout joints.

METHOD OF APPLICATION

Safety Data Sheet (SDS) must be read before opening the product.

Test First: Due to the nature of different surfaces, always do a test first in an inconspicuous area to determine surface colour stability and desired results

Ultra-grout sealer should only be used in open or well-ventilated areas or when respirator is worn.

1. Make sure the surface to be sealed is clean and free from grease, soap build up, paint, efflorescence, acids, grout and cement residue.
2. Shake can well before use and spray product directly to a clean dry surface from approximately 15-20cm away from surface. Apply in an even sweeping motion.
3. Avoid overspray which can cause the sealer to run & pool.
4. Porous surfaces may require more than one application. Allow a minimum of 30 minutes drying time between coats.
5. Surface will be ready for use in 2 hours, but keep surface dry for 24 hours until it fully cures.
6. Be sure to completely wipe surface dry within 5 minutes of each application using a white dry cloth or microfiber towel to remove any excess sealer.

PRECAUTIONS

- Read the label, SDS & Technical bulletin before use.
- Apply sealer when surface temperature is between 10 to 33 degrees Celsius.
- Ultra Grout Sealer is NOT a waterproofing agent. Water or moisture must not come into contact with newly sealed areas for at least 24 hours of application.
- Use in well ventilated areas

MAINTENANCE

The surface needs to be maintained with care. Spills should be cleaned up immediately to minimize absorption. Periodic cleaning of the surface should take place as follows:

- Rodaux Neutral bright - for regular cleaning
- Rodaux Heavy duty cleaner- for periodic heavy-duty cleaning

SAFETY

The Technical Bulletin in conjunction with Safety Data Sheet (SDS) and the product label have to be read and understood, prior to opening the container and use of the product

EXPECTED WEAR

The sealer lasts up to 5 years under standard conditions if due care is given. The products long term performance and lifetime expectancy can be affected by many factors;

- Location of the surface: In a high-traffic floor area, the impregnator wears away as the stone surface wears down. External surfaces may be subject to more natural weather conditions than internal surface therefore reducing the sealers lifetime.

Over time the sealers ability to protect the surface is also minimised due to its life span, type of stone and other external factors. (Based on the manufacturers recommendation and taking into consideration of the above factors.)

The sealer is not a barrier on top of the surface and will not protect from physical damages such as scratches and chips and also will not prevent 'etching' from acid spills.

LIMITATIONS

- Ultra Grout Sealer will not prevent surface wear or etching from acidic or highly alkaline chemicals.
- Remove any spills or contaminates immediately or within a reasonable time from the surface.
- Ultra Grout Sealer is not a waterproofing agent.
- Do not allow Ultra Grout Sealer to come into contact with any other surfaces other than the intended area to be sealed.

STORAGE AND HANDLING

- Close lid of bottle tightly after every use
- Store in a cool place
- Clean equipment and tools with water and do not re-use container.
- Refer to the Safety Data Sheet for further information.
- Do not re-use container.

ADVANCE NOTICE

The information provided in this Technical Bulletin is based on the present state to our best knowledge. The information herein is of a general nature, no assumption can be made as to a products suitability for a particular use of application. The owner / applicator is responsible for checking the suitability of products for their intended use

Rodaux Surface Care or any of its related entities cannot be held responsible and liable for:

- Inappropriate use of this product, other than that has been listed under the heading “suitable for”; and/or
- Incorrect application of this product that may lead to damage, discolour, surface wear, etching from acidic or alkaline chemicals; and/or
- Injuries, respiratory difficulties arising from not wearing appropriate eye, skin or any other protective wear.

Technical Bulletin is subject to change without notice, therefore all applicators should ensure they have the most current information and have familiarised themselves prior to the use of this product.

